



Compact low headroom trolley hoist with integrated push trolley model VNRP and model VNRG

Capacity 1500 - 24000 kg

On account of a special chain reeving system and corresponding chain guide the trolley hoist series VNR offers minimum headroom and maximum usage of the available room height. These hoists have been specially designed for heavy industrial applications.

Features

- All-steel construction with zinc-plated load and hand chains.
- All units are built to order for a predetermined beam dimension. They cannot be adjusted retro-actively to other beam sizes.
- Anti-drop and anti-tilt devices as standard.

Options

- Chain container
- Buffers

Technical data model VNRP and model VNRG

Model	Capacity kg	Lowest headroom hook dimension A mm	Curve radius min. m	Pull on hand chain at WLL daN	Weight kg
VNRP 1,5	1500	159	2.0	19	95
VNRP 2,0	2000	159	2.0	25	96
VNRP 3,0	3000	188	2.0	20	140
VNRP 4,0	4000	203	2.3	26	141
VNRP 5,0	5000	223	2.6	36	263
VNRP 6,0	6000	223	2.6	43	263
VNRP 8,0	8000	280	2.9	30	298
VNRP 10,0	10000	292	3.0	40	469
VNRP 12,0	12000	292	–	47	469
VNRP 16,0	16000	346	–	31	734
VNRP 20,0	20000	438	–	40	895
VNRP 24,0	24000	438	–	47	895
VNRG 1,5	1500	159	2.0	19	105
VNRG 2,0	2000	159	2.0	25	107
VNRG 3,0	3000	188	2.0	20	153
VNRG 4,0	4000	203	2.3	26	156
VNRG 5,0	5000	223	2.6	36	290
VNRG 6,0	6000	223	2.6	43	290
VNRG 8,0	8000	280	2.9	30	354
VNRG 10,0	10000	292	3.0	40	507
VNRG 12,0	12000	292	–	47	507
VNRG 16,0	16000	346	–	31	771
VNRG 20,0	20000	438	–	40	968
VNRG 24,0	24000	438	–	47	968