



Spreader beam for box pallets model TTS

Capacity 1000 - 3000 kg

Box pallets with DIN 15155 specifications, are usually moved around with a forklift, but are so sturdy that they can be picked up and transported with a spreader beam grab and an overhead crane hooked up to the top of the box pallet's frame.

Thanks to these spreader beams, the shipping and receiving area is no longer entirely dependent on floor-level material handling equipment such as forklifts.

The version designed for the individual transport of box pallets is equipped with two fixed yokes and two pivoted ones, interconnected with a control bar. The load tackling gear is fixed and unfixed by only one person.

**When using these spreader beams,
it is important that the hooks be fastened
only to the top frame of the box pallets.**

Technical data model TTS

| Model | EAN-No. 4025092* | Capacity kg | Weight kg |
|--------------------|---------------------|----------------|--------------|
| TTS 1,0/1240 - 810 | *551595 | 1000 | 38 |
| TTS 2,0/1240 - 810 | *551236 | 2000 | 61 |
| TTS 3,0/1240 - 810 | *553742 | 3000 | 80 |

Dimensions model TTS

| Model | TTS 1,0/1240 - 810 | TTS 2,0/1240 - 810 | TTS 3,0/1240 - 810 |
|-------|--------------------|--------------------|--------------------|
| A, mm | 1175 | 1175 | 1175 |
| B, mm | 600 | 600 | 600 |
| C, mm | 410 | 495 | 520 |
| D, mm | 195 | 215 | 215 |
| E, mm | 125 | 180 | 205 |
| F, mm | 100 | 150 | 170 |
| G, mm | 80 | 100 | 130 |
| H, mm | 28 | 30 | 40 |
| I, mm | 15 | 20 | 25 |

