

Technical data model SW-E BETA PROLINE

Art.-No.	Size	Capacity 1 st layer	Capacity top layer	Lifting speed 1 st layer	Lifting speed top layer	Rope diameter*	Recom- mended rope tensile strength N/mm ²	Motor	Classifi- cation	Useable rope length 1 st layer	Useable rope length top layer	Weight without rope
		kg	kg	m/min	m/min	mm		kW	FEM/ISO	m	m	kg
031148012	1	250	212	9.5	11.2	5	1770	0.42	2m/M5	16.2	77.8	62
031148018	1	250	212	13.8	16.4	5	1770	0.60	2m/M5	16.2	77.8	63
031148024	1	250	212	19.0	23.0	5	1770	0.93	2m/M5	16.2	77.8	64
031148007	1	320	272	6.0	7.1	5	1960	0.32	2m/M5	16.2	77.8	63
031148013	1	320	272	9.6	11.3	5	1960	0.54	2m/M5	16.2	77.8	63
031148019	1	320	272	13.8	16.4	5	1960	0.77	2m/M5	16.2	77.8	64
031148025	1	320	272	21.3	25.8	5	1960	1.19	2m/M5	16.2	77.8	67
031148077	1	500	343	8.5	12.6	6	1960	0.75	1Am/M4	8.4	58.5	64
031148208	2	500	414	10.3	12.5	8	1770	0.91	2m/M5	17.1	85.5	104
031148209	2	630	522	10.3	12.5	8	1770	1.14	2m/M5	17.1	85.5	104
031148219	2	630	522	20.3	24.8	8	1770	2.25	2m/M5	17.1	85.5	111
031148205	2	800	663	4.8	5.7	8	1960	0.67	2m/M5	17.1	85.5	101
031148210	2	800	663	10.3	12.5	8	1960	1.45	2m/M5	17.1	85.5	104
031148220	2	800	663	20.5	25.0	8	1960	2.87	2m/M5	17.1	85.5	114
031148259	2	980	689	7.5	10.7	9	1960	1.28	1Am/M4	11	77.4	104
031148403	3	1250	1066	5.2	6.2	12	1770	1.15	2m/M5	16.3	61.3	165
031148406	3	1250	1066	11.5	13.6	12	1770	2.41	2m/M5	16.3	61.3	174
031148441	3	1600	1100	8.5	12.5	12	1960	2.28	1Am/M4	12.1	87.7	174
031148444	3	1600	1100	11.5	17.0	12	1960	3.50	1Am/M4	12.1	87.7	173
031148504	3.5	2000	1667	7.6	9.6	14	1770	2.66	2m/M5	13.8	53.9	221
031148507	3.5	2000	1667	10.6	12.9	14	1770	3.89	2m/M5	13.8	53.9	234
031148510	3.5	2000	1667	16.3	20.3	14	1770	5.72	2m/M5	13.8	53.9	246
031148505	3.5	2500	2083	7.6	8.9	14	1770	3.35	2m/M5	13.8	53.9	224
031148502	3.5	2500	2083	5.5	6.5	14	1770	2.40	2m/M5	13.8	53.9	221
031148511	3.5	2500	2083	16.3	20.3	14	1770	7.15	2m/M5	13.8	53.9	246
031148530	3.5	3200	2354	4.5	6.1	14	2160	2.52	1Am/M4	11.4	64.5	221
031148536	3.5	3200	2354	8.7	12.0	14	2160	5.10	1Am/M4	11.4	64.5	234
031148620	4	3200	2647	22.1	27.2	18	1770	12.19	2m/M5	15.6	62	503
031148644	4	4000	2664	5.7	8.7	18	1960	4.38	1Am/M4	12.7	98.3	435
031148652	4	4000	2664	11.2	17.2	18	1960	7.85	1Am/M4	12.7	98.3	468
031148802	5	5000	4207	3.9	4.6	20	1960	3.66	2m/M5	20.3	79.2	1047
031148804	5	5000	4207	8.1	9.7	20	1960	7.58	2m/M5	20.3	79.2	1019
031148823	5	6300	4690	3.4	4.3	20	2160	3.72	1Am/M4	16.4	93.4	1047
031148825	5	6300	4690	6.5	8.8	20	2160	7.71	1Am/M4	16.4	93.4	1019
031148840	5	7500	4810	5.3	8.3	20	2160	7.44	1Bm/M3	13.4	104.8	1019
031148842	5	7500	4810	10.4	16.4	20	2160	13.46	1Bm/M3	13.4	104.8	1098

*recommended rope: DIN 3069 SE-znk 1960, non-rotating



! Pfaff winches are not designed for passenger elevation applications and must not be used for this purpose.