



## Plate clamp with hinged hook ring model Shark-S

Capacity 1000 - 3000 kg

### Features

- For the toughest operating conditions.
- This clamp is primarily used for transporting single steel plates in the vertical position, as well as lifting and turning through 180°, up to a surface hardness of HRC 40.
- With hinged hook ring to be used as a two-legged lifting system (see diagram of forces).
- Quality as yet unknown for plate clamps, guarantees highest safety standards and an extremely long service life.
- Fulfills the requirements of all relevant standards and EU-Directives.

### Options

- Special jaws for a surface hardness up to HRC 50. Especially for alloyed / stainless steel and slippery surfaces.

**The min. load is 10 %  
of the nominal WLL!**

**The surface hardness of the material must not  
exceed HRC 40.**

### Technical data model Shark-S

| Model       | EAN-No.<br>4025092* | Capacity<br>kg | Jaw capacity Z<br>mm | Weight<br>kg |
|-------------|---------------------|----------------|----------------------|--------------|
| Shark-S 1,0 | *558822             | 1000           | 0 - 20               | 3.6          |
| Shark-S 2,0 | *558839             | 2000           | 0 - 32               | 7.8          |
| Shark-S 3,0 | *197984             | 3000           | 0 - 32               | 8.3          |

### Dimensions model Shark-S

| Model   | Shark-S 1,0 | Shark-S 2,0 | Shark-S 3,0 |
|---------|-------------|-------------|-------------|
| A, mm   | 120         | 170         | 170         |
| B, mm   | 248         | 349         | 378         |
| Ø C, mm | 38          | 65          | 80          |
| D, mm   | 42          | 58          | 58          |
| E, mm   | 60          | 80          | 80          |
| F, mm   | 72          | 88          | 88          |
| G, mm   | 58          | 69          | 69          |
| H, mm   | 12          | 19          | 19          |
| I, mm   | 13          | 20          | 20          |
| J, mm   | 137         | 191         | 191         |
| K, mm   | 152         | 214         | 214         |
| L, mm   | 223         | 326         | 336         |

