

## Shock-absorbing lanyard model BFD-K

Conform to EN 355

- Abrasion-proof webbing with energy absorber.
- Width 30 mm
- End connections:
  - 1 x screw gate snap hook, opening 18 mm,
  - 1 x standard snap hook, opening 18 mm.



### Technical data model BFD-K

| Model     | EAN-No.<br>4025092* | Length<br>m |
|-----------|---------------------|-------------|
| BFD-K 1,5 | *188494             | 1.5         |
| BFD-K 2,0 | *165327             | 2.0         |

## Shock-absorbing lanyard model BFD-R

Conform to EN 355

- Abrasion-proof webbing with energy absorber.
- Width 30 mm
- End connections:
  - 1 x standard snap hook, opening 18 mm,
  - 1 x scaffold hook, opening 60 mm.



### Technical data model BFD-R

| Model     | EAN-No.<br>4025092* | Length<br>m |
|-----------|---------------------|-------------|
| BFD-R 1,5 | *188500             | 1.5         |
| BFD-R 2,0 | *165341             | 2.0         |

## Twin-tail shock-absorbing lanyard model BFD-T

Conform to EN 355

- Abrasion-proof twin-tail webbing with energy absorber.
- Width 30 mm
- End connections:
  - 1 x standard snap hook, opening 18 mm,
  - 2 x scaffold hook, opening 60 mm.



### Technical data model BFD-T

| Model | EAN-No.<br>4025092* | Length<br>m |
|-------|---------------------|-------------|
| BFD-T | *165334             | 2.0         |