

Fall arrest block model HSG-S

Conform to EN 360

- Plastic housing
- Fall indicator
- Galvanized steel rope (diameter 4 mm).
- Rope lengths 6 up to 28 m.
- End connection:
screw gate snap hook AXK 10 SI, opening 23 mm
- Useable up to 120 kg

Technical data model HSG-S

Model	EAN-No. 4025092*	Length m	Weight kg	Dimensions mm
HSG-S-6	*165006	6.0	5.10	208x85x280
HSG-S-10	*165013	10.0	5.30	208x85x280
HSG-S-15	*165020	15.0	6.10	208x85x280
HSG-S-20	*165037	20.0	11.25	260x120x340
HSG-S-25	*165044	25.0	11.50	260x120x340
HSG-S-28	*165068	28.0	11.65	260x120x340



Fall arrest block model HSG-G

Conform to EN 360

- Plastic housing
- Fall indicator
- Abrasion-proof 45 mm wide webbing with energy absorber.
- End connections:
1 x screw gate snap hook, opening 18 mm,
1 x screw gate snap hook AXK 10 S, opening 22 mm.
- Useable up to 120 kg

Technical data model HSG-G

Model	EAN-No. 4025092*	Length m	Weight kg	Dimensions mm
HSG-G	*165075	2.25	1.2	115x80x150

